



FLEETFLIX™
SEE WHAT'S AHEAD

FLEETFLIX LITE



PRODUCT DESCRIPTION

INTRODUCING FLEETFLIX LITE ROAD FACING DASH CAMERA — YOUR GO-TO SOLUTION FOR OPTIMIZING FLEET MANAGEMENT. THIS CUTTING-EDGE DASHCAM IS DESIGNED TO EMPOWER DRIVER PRIVACY AND STREAMLINE FLEET OPERATIONS, ENHANCING OVERALL EFFICIENCY.

FLEETFLIX LITE GOES BEYOND TRADITIONAL DASHCAMS, OFFERING REAL-TIME AND PRECISE VEHICLE POSITION INFORMATION ALONG WITH COMPREHENSIVE OPERATIONAL DATA TRANSMITTED DIRECTLY TO THE FLEET MANAGEMENT PLATFORM. STAY IN CONTROL WITH INSTANT ACCESS TO CRUCIAL INSIGHTS, ALLOWING FOR INFORMED DECISION-MAKING AND OPTIMAL RESOURCE ALLOCATION.

WITH HIGH-QUALITY REMOTE INTERCOM FUNCTIONALITY, FLEETFLIX LITE FOSTERS SEAMLESS COMMUNICATION BETWEEN DRIVERS AND THE FLEET MANAGEMENT TEAM. EXPERIENCE THE CONVENIENCE OF VIDEO LIVE VIEW PLAYBACK, MAKING IT EASIER THAN EVER TO REVIEW AND ANALYZE EVENTS ON THE ROAD.

MAKE THE SMART CHOICE FOR YOUR FLEET — INVEST IN FLEETFLIX LITE ROAD FACING DASH CAMERA AND ELEVATE YOUR FLEET MANAGEMENT TO NEW HEIGHTS. EFFICIENT, RELIABLE, AND TECHNOLOGICALLY ADVANCED — IT'S TIME TO DRIVE SUCCESS WITH FLEETFLIX LITE.

PRODUCT FEATURES

- ULTRA-WIDE 143° ROAD FACING LENS, UP TO 1080P UHD VIDEO RECORDING
- UP TO 1TB OF STORAGE, UTILIZING 2 × 512GB DUAL MICRO SD CARDS FOR CONTINUOUS OR BACK UP
- 2 CHANNEL VIDEO RECORDING
- BUILT-IN WI-FI, 4G COMMUNICATION MODULE, AND INERTIAL NAVIGATION POSITIONING MODULE
- 4-CHANNEL IO INPUT, 1-CHANNEL CAN AND 1-CHANNEL RS232
- COMPACT DESIGN THAT DOESN'T AFFECT THE DRIVER'S SIGHT
- OBD PLUG N PLAY INSTALLATION
- SLEEP MODE, REMOTE WAKEUP
- SUPPORTS RAPID ACCELERATION, RAPID DECELERATION, HARSH CORNERING, AND ACCIDENT DETECTION
- FULLY INTEGRATED INTO GEOTAB

PRODUCT SPECIFICATIONS

- | | |
|-----------------------------|--|
| • DIMENSIONS | • POWER SUPPLY |
| 4.44 IN X 2.66 IN X 2.24 IN | 12V AND 24V VEHICLES |
| 113.0 MM X 67.8 MM X 57 MM | |
| • WEIGHT | • WIFI |
| 0.584LBS | SUPPORTS 2.4G |
| 265G | |
| • OPERATING TEMPERATURE | • IP RATING |
| 40°F +158°F | IP30 |
| 40°C +70°C | |
| | • CONNECTIVITY |
| | 4G LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 |
| | WCDMA: B2/B4/B5 |